

KNAF minimum Safety requirements 2025

(see also KNAF Reglementen Boek 2025, Algemeen Autorensport Reglement, Reglement: Clubsport, Articles 12 & 13)

Safety requirements drivers equipment (Art 13):

Clothing according to CSI appendix L with FIA norm 8856-2000 (or higher 8856-2018)

- Overall FIA norm 8856-2000 (with FIA hologram)
- Balaclava FIA norm 8856-2000 (with FIA hologram)
- Underwear FIA norm 8856-2000 (with FIA hologram)
- Shoes FIA norm 8856-2000 (with FIA hologram)
- Gloves FIA norm 8856-2000 (with FIA hologram)
- Socks FIA norm 8856-2000

Helmets (crash helmets) according to CSI appendix L with norm (see FIA TL25);
FIA 8859-2015, FIA 8860-2010 (not valid after 31-12-2028) and FIA 8860-2018,
preferable (but not obligatory) an FHR system.

Safety requirements Cars (Art 12):

- Seatbelts: 5- or 6-point seatbelt FIA standard 8853/98 or higher (age limited to 5 year after label expiry date). When a harness is labeled as "For FHR use only" the use of an FHR system is compulsory, and the age is limited to the label expiry date.
- Fire extinguisher: CSI appendix J article 253.7.2 and 7.3.
- Safety cage (ROPS):
 - o Touringcars & GT's: CSI appendix J article 253.8
 - o Formula cars & Sportscars: CSI appendix J (2013), article 277, article 253.8 and 259.16.4.
 - o Protective padding FIA 8807-2001 type A (FIA TL 23) according to App J 253.8.3 and drawing 253-68.
 - o Rollbars with so-called S-shape / double bend in the front rollbar are no longer tolerated.
- Windonet conform CSI appendix J article 253.11 is compulsory. An arm restraint (conform SFI 14.2 or 3.3) may be added.
- External circuit breaker: CSI appendix J article 253.13
- Fuel tanks & fillers: CSI appendix J, article 253.14: Original tank or FT3 1999, FT3,5 or FT5 tank with FIA approval within date of validity.
- Seats: CSI appendix J article 253.16, FIA norm 8855-1999 with maximum age of 10 year or FIA 8862-2009 also maximum age of 10 year or FIA 8855-2021.
- Seat mounting with minimum 4 fixation points, using bolts with minimum diameter of 8 mm, quality 8.8 (ISO-norm) or higher and mounting plates of minimum 40 cm² at each fixation point (min. thickness for steel 3 mm, for aluminum 5 mm).
- FIA rainlight is compulsory, CSI Appendix J article 259.8.4.4 (FIA TL19).

For all Cars participating competitions run conform CSI appendix K, all Cars need to comply with the safety requirements as stated in CSI appendix K.